

# MATERIAL SAFETY DATA SHEET

## 1 IDENTIFICATION

Product name :JP-K32A  
 Name of company :Hitachi Industrial Equipment Systems Co., Ltd  
 Address :1-1,Higashitaga-cho 1-chome, Hitachi-shi, Ibaraki-ken, Japan  
 Tel :+81-294-36-8682  
 Fax :+81-294-36-8975  
 Recommended use of the chemical  
 and restrictions on use :Printing Ink for industrial Marking

## 2 HAZARDS IDENTIFICATION

Physico-chemical endpoints :Flammable liquid Category 2  
 Acute toxicity - oral :Not available  
 Acute toxicity - dermal :Not identified  
 Acute toxicity - inhalation (air) :Not identified  
 Acute toxicity - inhalation (vapors) :Not available  
 Acute toxicity - inhalation (dust, mist) :Not available  
 Skin corrosion/irritation :Not available  
 Eye damage/irritation :Category 2  
 Sensitization - respiratory :Not identified  
 Sensitization - skin :Not identified  
 Germ cell mutagenicity :Category 1  
 Carcinogenicity :Not available  
 Toxic to reproduction :Category 1  
 Effects on or via lactation :Not identified  
 Specific target organ systemic toxicity  
 (Single exposure) :Category 3 Respiratory system,anesthetizing action  
 (Repeated exposure) :Category 1 liver  
 :Category 2 nervous  
 Aspiration toxicity :Not identified  
 Hazardous to the aquatic environment  
 -Acute hazard :Not available  
 -Chronic hazard :Not available

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

**GHS label elements**

Hazard symbols: Flame, Exclamation mark, Health hazard

**Signal word:** Danger**Hazard statement and precautionary statement:**

- Highly flammable liquid and vapour
- Causes eye irritation
- May cause bad effect to genetic or fetus
- May damage fertility or the unborn child
- May cause respiratory irritation-single exposure
- Causes damage to liver-through prolonged or repeated exposure
- May causes damage to nervous-through prolonged or repeated exposure

**Precautionary statements:**

- Keep out of reach of children. Read label before use. If medical advice is needed: Have product container or label at hand.

**Prevention**

- Keep away from ignition sources such as heat/sparks/open flame— No smoking.
- Take precautionary measures against static discharge.
- Wear protective gloves and eye/face protection as specified by the competent authority.
- Do not breathe dust/mist/vapors.
- Use only in a well-ventilated area. Call a doctor/physician if you feel unwell.
- Do not eat, drink or smoke when using this product.
- Avoid contact during pregnancy/while nursing.
- Wash hands thoroughly after handling.

**Response**

- In case of fire, use dry chemical, CO<sub>2</sub>, water splay (fog) or foam for extinction.
- IF SWALLOWED: Call a doctor/physician if you feel unwell. Rinse mouth.
- IF ON SKIN: Gently wash with plenty of soap and water.
- Wash/Decontaminate removed clothing before reuse.
- If skin irritation occurs, seek medical advice/attention.
- IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor/physician.
- Collect spillage.

**Storage**

- Store in cool/well-ventilated place. Store locked up.
- Call a doctor/physician if exposed or you feel unwell.

**Disposal**

---

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

- Waste must be disposed of according to applicable regulations.

### 3 Composition/information on ingredients

**Substance or mixture;** mixture

**Composition;**

Chemical name	concentration (%)	CAS number
Ethanol	75-85	64-17-5
Chrome -Complex Dye	5-10	TSCA Registered

### 4 First-aid measures

**Inhalation;**

Remove the victim from the contamination immediately to fresh air. Keep the victim warm and quiet and arrange for transport to the nearest medial facility for examination and treatment by a physician as soon as possible.

**Skin contact;**

Remove all contaminated clothing, shoes and socks from the affected areas as quickly as possible. Wash the affected area under running water using a mild soap. If irritation persists, arrange for transport to the nearest medical facility for examination and treatment by a physician as son as possible.

**Eye contact;**

Gently rinse the affected eyes with clean water for at least 15 minutes. Remove contact lenses if easily possible. and refer for medical attention.

**Ingestion;**

Never give anything by mouth to someone who is unconscious or convulsing. If the victim is responsive, give him one or two glasses of water. And refer for medial attention.

### 5 Fire-fighting measures

**Suitable extinguishing media;**

Use dry chemical, CO<sub>2</sub>, water splay (fog) or form.

**Fire fighting procedures;**

Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors.

Avoid spraying water directly into storage containers due to danger of boil over.

**Unusual fire/explosion hazard;**

Flammable liquid, can release vapors that form flammable mixtures at temperatures at or above the flashpoint.

**Special protective equipment and precautions for fire fighters;**

Fire fighters should wear boots, overalls, gloves, eye and face protection and breathing apparatus.

### 6 Accidental release measures

Shut off all sources of ignition; No smoking or flames in area. Absorb spill with inert material (e.g., dry sand or earth), then place in closed containers using non-sparking tools. Flush residual spill (area) with copious amounts of water.

---

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

## 7 Handling and storage

### Handling;

Use only in the well-ventilated areas.  
Make available in the work area emergency shower and eyes wash.  
Avoid contact with skin or eyes.

### Storage;

Close up the container and keep it in dark cool(0~20 ) place.  
Keep away from combustible materials and sources of ignition.

## 8 Exposure controls/personal protection

### Exposure guidelines;

ACGIH TLV-TWA (ppm)	
Ethanol	:1000
Chrome -Complex Dye	:None known
ACGIH STEL(ppm)	
Ethanol	:No data
Chrome -Complex Dye	:None known

## 9 Physical and chemical properties

Appearance	
Physical state	:Liquid
Color	:Black
Odor	:Solvent odor
Boiling point	: 78.3 (ethanol)
Flash point	:15.1 (closed cup)
Upper/lower flammability or explosive limits	:Lower 4.3 vol%, Upper 19 vol%(ethanol)
Vapor pressure	: 5.9kPa(20 )(ethanol)
Relative density (Air = 1)	:1.59(ethanol)
Relative density	:0.85(20 )
Solubility(Water)	:water;infinite(ethanol)
Partition coefficient: n-octanol/water	:-0.32(ethanol)
Auto-ignition temperature	:390 (ethanol)
Decomposition temperature	:No measurement

## 10 Stability and reactivity

Stability: The product is stable.  
Conditions and materials to avoid: Not available  
Hazardous decomposition products: These products are carbon oxides

## 11 Toxicological information

### Acute toxicity;

Ethanol  
Not available:Oral 6.2 ~ 17.8 (Rat LD50 (g/kg))

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Not identified: Dermal No data

Not available: Inhalation 31600 (Vaper) (Rat LC50(ppm/4h))

Chrome -Complex Dye

Oral >5000 (Rat LD50 (mg/kg))

Dermal >2000 (Rat LD50 (mg/kg))

Inhalation None known

**Skin corrosion/irritation;**

Ethanol

Not identified

Chrome -Complex Dye

No (Rabbit test-OECD404 1981)

**Serious eye damage/irritation;**

Ethanol

Category 2A

Chrome -Complex Dye

No (Rabbit test-84/449/EEC B.5)

**Respiratory or skin sensitization;**

Ethanol

Not identified

Chrome -Complex Dye

No (Guinea pig test-84/449/EC B.6)

**Germ cell mutagenicity;**

Ethanol

Category 1B

Chrome -Complex Dye

Not identified

**Carcinogenicity;**

Ethanol

Not available Oral 6.2 ~ 17.8 (Rat LD50 (g/kg))

Chrome -Complex Dye

Not identified

**Reproductive toxicity;**

Ethanol

Category 1A

Chrome -Complex Dye

Not identified

**STOST-single exposure;**

Ethanol

Category 3 (Respiratory)

Chrome -Complex Dye

Not identified

**STOST-repeated exposure;**

Ethanol

Category 1 (Liver) 2 (Nervous system)

Chrome -Complex Dye

None known

**Aspiration hazard.**

Ethanol

Not identified

---

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Chrome -Complex Dye  
None known

## 12 Ecological information

### Toxicity:

Ethanol  
trout 24h-LC50 (g/L):11.2  
Carp 96h-LC50 (g/L):18 ~ 13.4  
Creek Chub 24h-C50(g/L):7  
Guppy 7d-LC50(g/L):11  
Chrome -Complex Dye  
Carp LC50(mg/L):2  
Daphnia EC50(mg/L):1000 (Darp.Mag Straus 1820 test)

### Persistence and degradability:

Ethanol  
None known  
Chrome -Complex Dye  
None known

### Bioaccumulative potential:

Ethanol  
None known  
Chrome -Complex Dye  
None known

### Mobility in soil:

Ethanol  
None known  
Chrome -Complex Dye  
None known

## 13 Disposal considerations

Scrap materials may be disposed by licensed contractor or burn in an approved incinerator.  
Do not dump into sewer, on the ground or into any body of water.  
Follow national and local regulations.

## 14 Transport information

Follow all regulations in your country.

UN Number	:1210
UN Proper Shipping Name	:Printing ink, flammable
Transport hazard class	:Class 3(Flammable liquid)
Packing Group	:
Environmental hazards	:No

## 15 Regulatory information

Follow all regulations in your country.  
Content of RoHS Directive material Cd<100ppm Pb, Hg, Hexavalent Cr, PBB, PBDE<1000ppm

## 16 References

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

- 1) Solvent, dye MSDS
- 2) Results of Eco-toxicity tests of chemicals conducted by Ministry of the Environment in Japan (-2006)
- 3) International Chemical Safety Cards

---

To the best of our knowledge, the information contained here in is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.