Issue 2015.12.21 Revision 2023.03.17

## Safety Data Sheet (SDS)

## Section 1 - CHEMICALS AND COMPANY IDENTIFICATION

COMPANY IDENTIFICA	FION
Chemical Identifier	Ink-1304K
Product Code	1304K
Reference Number	52
Name of Supplier	Hitachi Industrial Equipment Systems Co.,Ltd.
Address	1–1 Higashitaga-cho 1-chome,Hitachi-shi, Ibaraki-ken, 316-8502 Japan
Company Contact	IJP ink Group, Marking Systems and Hoist Systems Division
Phone Number	+81-294-36-8682
	+81-294-36-8975
	ogino-masahiko@hitachi-ies.co.jp
Emergency Phone Number	+81-294-36-8682
Recommended Use	Industrial ink jet printers
ICATION hemical	
Physicochemical	Flammable liquids Category 2
	Acute toxicity (Inhalation: vapour) Category 4
	Skin corrosion/irritation Category 2
	Serious eye damage/eye irritation Category 2A
	Specific target organ toxicity (single exposure)
	Category 2(kidney)
	Specific target organ toxicity (single exposure)
	Category 3(narcotic effect respiratory tract irritation)
	Specific target organ toxicity (repeated exposure) Category 1(nervous system)
Environmental Hazards	Hazardous to the aquatic environment, short-term (acute) Category 2
	Other hazards than mentioned above are Not classified or Classification not possible.
Pictograms	
	$\wedge$ $\wedge$ $\wedge$
Signal Word	Danger
Hazard Statements	H225 Highly flammable liquid and vapour
	H315 Causes skin irritation
	H319 Causes serious eye irritation
	H332 Harmful if inhaled
	H335 May cause respiratory irritation
	H336 May cause drowsiness or dizziness
	H371 May cause damage to kidney
	H372 Causes damage to nervous system through
	prolonged or repeated exposure
	H401 Toxic to aquatic life
Precautionary Statem	ents
Prevention	Keep away from heat, hot surfaces, sparks, open flames
	and other ignition sources. No smoking.(P210)
	Keep container tightly closed.(P233)
	Ground and bond container and receiving equipment.(P240)
	•••
	Chemical Identifier Product Code Reference Number Name of Supplier Address Company Contact Phone Number Fax Number Mail Address Emergency Phone Number Recommended Use CATION hemical Physicochemical Health Hazards Environmental Hazards Pictograms Signal Word Hazard Statements

	Use explosion-proof electrical, ventilating and lighting equipment.(P241)
	Use non-sparking tools.(P242)
	Take action to prevent static discharges.(P243)
	Do not breathe dust/fume/gas/mist/vapours/spray.(P260)
	Avoid breathing dust/fume/gas/mist/vapours/spray.(P261)
	Wash hand thoroughly after handling.(P264)
	Wash eye thoroughly after handling.(P264)
	Do not eat, drink or smoke when using this product.(P270)
	Use only outdoors or in a well-ventilated area.(P271)
	Avoid release to the environment.(P273)
	Wear protective gloves/protective clothing/eye protection/face protection.(P280)
Response	IF ON SKIN: Wash with plenty of soap and water.(P302+P352)
	IF ON SKIN or hair: Take off immediately all contaminated clothing. Rinse skin with water or shower.(P303+P361+P353)
	IF INHALED: Remove person to fresh air and keep comfortable for breathing.(P304+P340)
	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.(P305+P351+P338)
	IF exposed or concerned: Call a doctor.(P308+P311)
	Call a doctor if you feel unwell.(P312)
	Get medical advice and attention if you feel unwell.(P314)
	Specific treatment.(P321)
	If skin irritation occurs: Get medical advice/attention.(P332+P313)
	If eye irritation persists: Get medical advice/attention.(P337+P313)
	Take off contaminated clothing and wash it before reuse.(P362+P364)
	In case of fire: Use appropriate media to extinguish.(P370+P378)
Storage	Store in a well-ventilated place. Keep container tightly closed.(P403+P233)
	Store in a well-ventilated place. Keep cool.(P403+P235)
	Store locked up.(P405)
Disposal	Dispose of contents and container in accordance with local, regional and national regulations (to be specified).(P501)

Section 3 – COMPOSITION / INFORMATION ON INGREDIENTS Distinction of Substance or Mixture

Mixture		Mixture			
Chemical Name or Generic	Concentration or Its	Formula	ENCS No./I	SHL No.	CAS RN
Name	Ranges (%)		ENCS No.	ISHL No.	
Methyl ethyl ketone	70–75	CH3CH2CO CH3	(2)-542	Registered	78-93-3
Chromium and its compounds	3–5		Registered( Trade secret)	Registered( Trade secret)	Trade secret

Section 4 - FIRST AID MEASURES	
Inhalation	IF INHALED: Remove to fresh air and keep at rest in a
	position comfortable for breathing.
	IF exposed or concerned: Call a doctor.
Skin Contact	IF ON SKIN (or hair): Remove/Take off immediately all
	contaminated clothing. Rinse skin with water/shower.
	IF ON SKIN: Wash with plenty of soap and water.
	· · · · · · · · · · · · · · · · · · ·
	If skin irritation occurs: Get medical advice and attention.
	Specific treatment.
5.0.1	IF exposed or concerned: Call a doctor.
Eye Contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to
	do. Continue rinsing.
	If eye irritation persists: Get medical advice/attention.
Ingestion	IF exposed or concerned: Call a doctor. Rinse mouth.
Ingestion	IF SWALLOWED: Call a doctor if you feel unwell.
	IF exposed or concerned: Call a doctor.
Section 5 – FIRE FIGHTING MEASURES	
Suitable Extinguishing	Use extinguishing agent suitable for type of surrounding
Media	fire.
	When dust occurs, use dry sand.
Unsuitable Extinguishing Media	Cylindric water.
Specific Hazards in Case of	Risk of producing harmful gases such as carbon
Fire	monoxide. Avoid inhalation of smoke or gases.
Specific Fire Fighting	Fight fire from upwind position if possible
	Keep away from sources of ignition and use appropriate extinguishing media.
	Prohibit unauthorized staff from entering the area
	around the fire.
Special Protective	Keep unnecessary people away. Use goggles in combination with dust mask, and another
Equipment and Precautions	protections as appropriate to situation.
for Fire Fighters	F
Section 6 - ACCIDENTAL RELEASE MEASURES Personal Precautions,	Use goggles in combination with dust mask, and another
Protective Equipment and	protections as appropriate to situation.
Emergency Procedures	
	Large spills :Evacuate area.
Environmental Precautions	Ensure adequate ventilation. Do not discharge into the drains, surface waters or
	ground water directly.
Methods and Equipment for	No information available
Containment and Cleaning Up	
Prevention Measures for	Keep away from sources of ignition and prepare
Secondary Accidents	extinguishing media.
Section 7 - HANDLING AND STORAGE	
Handling Technical Measures	Provide ventilation system and use necessary personal
-	protective equipment as described in "Section 8 -
	EXPOSURE CONTROLS / PERSONAL PROTECTION".
	Ground/bond container and receiving equipment.
	Use only non-sparking tools.
	Use explosion-proof electrical/ventilating/lighting.

As far as we know, the information that is listed here is accurate. However, the above-mentioned suppliers or their subsidiaries shall not be liable for the accuracy or completeness of the information described above.

		Take precautionary measures against static discharge.
		Use local exhaust ventilation in case of production of fume or mist. Facilities storing or utilizing this material should be
		equipped with an eyewash facility and a safety shower.
	Precautions for Safe Handling	Wear protective gloves/eye protection/face protection.
	e e	Do not eat, drink or smoke when using this product.
		Wash hands thoroughly after handling.
		Use only outdoors or in a well-ventilated area. Keep cool.
		Do not breathe dust/fume/gas/mist/vapours/spray.
	Prevents Handling of Incompatible Substances or Mixtures	Refer to "Section 10 - STABILITY AND REACTIVITY".
Storage	Conditions for Safe Storage	Refer to "Section 10 - STABILITY AND REACTIVITY".
		Store locked up. Store container tightly closed in well-ventilated place.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

	Japan Administration Level	Exposure Limits (Japan Society for Occupational Health)	Exposure Limits (ACGIH)	
Methyl ethyl ketone	200ppm	200ppm(590mg/m3)	TWA 200 ppm, STEL 300 ppr	
Chromium and its	-	0.5mg/m3 as Cr3+	-	
compounds				
Engineering Controls		Use local exhaust ventila fume or mist.	ation in case of production of	
			ing this material should be h facility and a safety shower	
		Use explosion-proof elec from static electrocity.	strical equipment and prevent	
Personal Protective Equipment	Respiratory Protection	If necessary, wear respiratory protection.		
	Hand Protection	Wear protective gloves.		
	Eye/Face Protection	Wear eye protection/face protection.		
	Skin and Body Protection	Wear protective clothing		
tion 9 - PHYSICAL AND CHI	EMICAL PROPERTIES			
Physical State		Liquid		
Form		Liquid		
Colour		Black		
Odour		Solvent odor		
Melting Point/Freezing Point		-86.4°C (as 2-Butanone)	)	
Boiling Point or Initial Boiling Point and Boiling Ranges		79.6 °C (as 2-Butanone)		
Flammability		Flammability		
Lower and Upper Explosion Limit / Flammability Limit	Lower Limit	1.8vol% (as 2-Butanone)		
	Upper Limit	11.5vol% (as 2-Butanone	·	
Flash Point		-7.3°C (Tag Closed Cup	<b>`</b>	

Decomposition TemperatureNo data availablepHNo data availableKinematic Viscosity3.7mm2/sSolubilitywater: 29g/100mL (20°C) (as 2-Butanone)Partition Coefficient : n- Octanol/Water0.29(as 2-Butanone)Vapour Pressure10.5kPa (20°C) (as 2-Butanone)
pHNo data availableKinematic Viscosity3.7mm2/sSolubilitywater: 29g/100mL (20°C) (as 2-Butanone)Partition Coefficient : n-0.29(as 2-Butanone)Octanol/WaterOctanone)
Kinematic Viscosity3.7mm2/sSolubilitywater: 29g/100mL (20°C) (as 2-Butanone)Partition Coefficient : n-0.29(as 2-Butanone)Octanol/Water0.29(as 2-Butanone)
Solubilitywater: 29g/100mL (20°C) (as 2-Butanone)Partition Coefficient : n-0.29(as 2-Butanone)Octanol/Water0.29(as 2-Butanone)
Partition Coefficient : n- 0.29(as 2-Butanone) Octanol/Water
Octanol/Water
Vapour Pressure $10.5$ kPa ( $20^{\circ}$ C) (as $2-$ Rutanone)
Density and/or Relative 0.87 Density
Relative Gas Density 2.41 (Air=1, as 2-Butanone)
Particle Characteristics No data available
as Methyl ethyl ketone
Melting Point/Freezing -86.4°C
Boiling Point or Initial 79.6°C
Boiling Point and Boiling Ranges
Density and/or Relative 0.8061
Density
Section 10 – STABILITY AND REACTIVITY
Reactivity Does not react dangerously under nomal conditions.
Chemical Stability Stable under normal conditions of use.
Possibility of Hazardous Flammable
Reaction
Conditions to Avoid There is a risk of explosion due to impacts, friction, flame and
source of ignition. Incompatible Substances or No data available
Incompatible Substances or No data available Mixtures
Hazardous Decomposition No data available
Products
Other Data No data available
Section 11 – TOXICOLOGICAL INFORMATION
Acute Toxicity Oral Classified as Not classified since Category 5 is not
adopted in JIS Z 7252.
Classification not possible since lots of the concentrations of unknown ingredients.
Dermal Classification not possible since lots of the concentrations of unknown ingredients.
Inhalation (gas)
Does not fall under gas based on GHS definitions.
(vapour) Ola selfie di se Osta rese A sie se ATE is 2500 to
Classified as Category 4 since ATE is 2500 to 2000(ppmV).
(dust and mist)
Unable to classify due to insufficient data.
Skin Corrosion/Irritation Classified as Category 2 since the sum of Category 2
ingredients is more than 10%.
Serious Eye Damage/Eye Classified as Category 2A since the sum of 10×(Eye
Irritation Category 1 + Skin Category 1) is more than 10%.
Respiratory Sensitization Classification not possible since lots of the concentrations of unknown ingredients.
Skin Sensitization Unable to classify due to insufficient data.
Germ Cell Mutagenicity Classification not possible since lots of the
concentrations of unknown ingredients.

Carcinogenicity		Classification not possible since lots of the concentrations of unknown ingredients.
Reproductive Toxicity		(Reproductive toxicity) Unable to classify due to insufficient data. (Reproductive toxicity, effects on or via lactation)
Specific Target Organ Toxicity (Single Exposure)		Unable to classify due to insufficient data. Classified as Category 2(kidney) since one of the Category 2(kidney) ingredients is more than 10%.
		Classified as Category 3(narcotic effect) since the sum of Category 3(narcotic effect) ingredients is more than 20%.
		Classified as Category 3(respiratory tract irritation) since the sum of Category 3(respiratory tract irritation) ingredients is more than 20%.
Specific Target Organ Toxicity (Repeated Exposure)		Classified as Category 1(nervous system) since one of the Category 1(nervous system) ingredients is more than 10%.
Aspiration Hazard		Unable to classify due to insufficient data.
ection 12 - ECOLOGICAL INF Hazardous to the Aquatic Environment, Short-Term (Acute)	ORMATION	Classified as Category 2 since the sum of $(M \times 10 \times Category 1) + Category 2$ ingredients is more than 25%.
Hazardous to the Aquatic Environment, Long-Term (Chronic)		Classification not possible since lots of the concentrations of unknown ingredients.
Ecotoxicity Persistence Bioaccumulative Potential		No data available No data available No data available
Mobility in Soil Hazardous to the Ozone Layer		No data available Unable to classify due to insufficient data.
ection 13 - DISPOSAL CONSI	DERATIONS	
	Residual waste	Because waste materials such as liquid waste, paper towels used to wipe it up, or empty containers are flammable combustible materials the section on "specially controlled industrial waste(Flammable waste oil)" from the Waste Management and Public Cleaning Law (Waste Management Law) is applicable.
		Either appropriately process in accordance with Waste Management and Public Cleaning Law, or commission a contractor licensed for transport or disposal of industrial waste requiring special management.
		Do not let wastewater, etc. used for cleaning machinery or containers flow directly onto the groundor in to the culverts. For waste materials generated by wastewater treatment,
		incineration, etc. either carry out processingin accordance with the Waste Management and Public Cleaning Law and related laws and regulations, or commission a licensed vendor to do so.
		When incinerating of waste materials, etc., do not use an incinerato without cleaning equipment, as harmful gas will be generated.
	Contaminated containe	Clarify the contents of waste materials and entrust disposal to a waste disposal company. Empty containers should be treated as industrial wastes and not

Section 14 - TRANSPORT INFORMATION

International Regulations	Regulatory Information by Sea	Conform to the provisions of IMO.
	UN No.	1210
	Proper Shipping Name	PRINTING INK RELATED MATERIAL
	Class	3
	Packing Group	Π
	Marine Pollutant	Not applicable
	Liquid Substance	Not applicable
	Transported in Bulk	
	According to	
	MARPOL 73/78,	
	Annex II , the IBC Code	
	Code	
	Regulatory	Conform to the provisions of ICAO/IATA.
	Information by Air	
	UN No.	1210
	Proper Shipping Name	PRINTING INK RELATED MATERIAL
	Class	3
	Packing Group	Π
Regulations in Japan	Regulatory	Complies with the Fire Service Act.
	Information by Road	
	Regulatory	Conform to the provisions of the Ship Safety Law.
	Information by Sea	1010
	UN No.	
	Class	PRINTING INK RELATED MATERIAL 3
	Packing Group	I
	Marine Pollutant	Not applicable
	Liquid Substance	Not applicable
	Transported in Bulk	
	According to	
	MARPOL 73/78,	
	Annex II , the IBC	
	Code	
	Regulatory	Conform to the provisions of the Civil Aeronautics Law.
	Information by Air UN No.	1210
		PRINTING INK RELATED MATERIAL
	Class	3
	Packing Group	П
Emergency Response Guide		130
Number		
Section 15 - REGULATORY INF	ORMATION	
Industrial Safety and Health		Ordinance on the Prevention of Organic Solvent Poisoning
Act		Paragraph 1 Article 1 part 4 (Second-class organic solvents, etc.),
		Enforcement Ordinance 2 of Appendix 6
		the standards for work environment monitoring Article 65 $$ part 2–1 $$
		Dangerous or Harmful Substances Subject to Be Indicated their
		Names, etc.
		(Article 57 part 1 ,Order Article 18 part 1 and 2, Attached Table9)
		Dangerous Substances -Flammable substances(Order Article
		Appended Table 1 part 4)
		Hazardous Substances to be notified in terms of Whose Names,etc .(Article 57 part 2 ,Order Article 18 part 2-1and part 2, Attached
		Table9)
		Chromium and its compounds (excluding Chromic acid,
		Dichromic acid and its salts)(Number: 142) (less than 5%)
		Methyl ethyl ketone(Number: 570) (70%-80%)

Act

Materials for special medical examinations and current handling workers(Industrial Safety and Health Act66 2 and Order for Enforcement of Industrial Safety and Health Act Article 22 (i))

Poisonous and Deleterious Not applicable Substances Control Act Act on Confirmation, etc. of Not applicable Release Amounts of Specific Chemical Substances in the **Environment and Promotion** of Improvements to the Management Thereof Act on the Regulation of Priority Assessment Chemical Substances(Article 2 part 5) Manufacture and Evaluation of Chemical Substances Fire Service Act Hazardous Materials Category IV inflammable liquids Class I petroleums non water-soluble Packing Group II Water Pollution Prevention Specified substances (article 2, paragraph 4 of the Act, article 3 of the Enforcement Ordinance) raw materials for Narcotics or Psychotropics(Appended Table IV part Narcotics and **Psychotropics Control Act** 9, Order Article 4) Import Trade Control Order Appended Table I part 16 Foreign Exchange and Foreign Trade Act Import Trade Control Order Appended Table II (Import Approval ) Ship Safety Law Flammable liquids(Order Article 3, Appended Table I) Aviation Law Flammable liquids(Order Article 194, Appended Table I) Section 16 - OTHER INFORMATION Industrial Safety and Second-class organic solvents, etc.contain more than 5% of Second-Health Act class organic solvents. In the "15. Applicable laws" column, the materials for which label and SDS will be mandated are also listed. (Substance without a decree number.) Reiwa based on 0111 No. 1 from the Kiankahatsu, on January 11, 2022. ) 2-butanone and methyl ethyl ketone, MEK and ethyl methyl ketone are the same substances. Act on the Regulation We have a Priority Assessment Chemical Substance posting of Manufacture and threshold of 0.1% or more. Evaluation of **Chemical Substances** The posting of a Priority Assessment Chemical Substance in SDS is as of November 2019 as an effort. Foreign Exchange and In law, printing inks are not approved for export Foreign Trade Act Fire Service Act The flash point of Class I petroleums is less than 21  $\degree~$  c. Poisonous and The deleterious substances is only applicable to the material, and Deleterious the mixture is non-applicable. Substances Control Act Substances treated as equipment are exempt from this law. **RoHS Specified** Cd<100ppm Pb, Hg, Cr(VI), PBB, PBDE, DEHP, DBP, BBP, DIBP <1000ppm Substance Concentration Allowable TLV-TWA: Threshold Limit Values-Time Weighted Average STEL concentration (Short Term Exposure Limit JIS Z7253:2019 Standards **Cited Literature** 1) International Chemical Safety Cards 2) National Institute of Technology and Evaluation (NITE), Japan 3) Site for Safe Workplace by Ministry of Health, Labour and Welfare, Japan

## 4) EZSDS (JCDB)

about This Product:

Additional Information To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.