Issue 2017.11.22 Revision 2023.03.07

Safety Data Sheet (SDS)

Section 1 - CHEMICALS AND COMPANY IDENTIFICATION

Chemical Identifier Solvent-S1406

Product Code S1406 Reference Number 1026

Hitachi Industrial Equipment Systems Co., Ltd. Name of Supplier

Address 1-1 Higashitaga-cho 1-chome, Hitachi-shi, Ibaraki-ken,

316-8502 Japan

+81-294-36-8682

Company Contact IJP ink Group, Marking Systems and Hoist Systems Division

Phone Number +81-294-36-8682 Fax Number +81-294-36-8975

ogino-masahiko@hitachi-ies.co.jp Mail Address

Emergency Phone

Number

Recommended Use Industrial ink jet printers

Section 2 - HAZARDS IDENTIFICATION

GHS Classification of the Chemical

Physicochemical Flammable liquids Category 2

Health Hazards Acute toxicity (Inhalation: vapour) Category 4

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Carcinogenicity Category 1A Reproductive toxicity Category 1A

Specific target organ toxicity (single exposure) Category 2(kidney systemic toxicity central nervous

system)

Specific target organ toxicity (single exposure) Category 3 (narcotic effect respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Category 1 (liver nervous system)

Specific target organ toxicity (repeated exposure) Category 2(blood central nervous system)

Other hazards than mentioned above are Not classified or Classification not possible.

GHS Label Elements

Pictograms



Signal Word Hazard Statements

Danger

H225 Highly flammable liquid and vapour

H315 Causes skin irritation

H319 Causes serious eye irritation

H332 Harmful if inhaled

H335 May cause respiratory irritation H336 May cause drowsiness or dizziness

H350 May cause cancer

H360 May damage fertility or the unborn child

H371 May cause damage to kidney, systemic toxicity,

central nervous system

H372 Causes damage to liver, nervous system through

prolonged or repeated exposure

H373 May cause damage to blood, central nervous system through prolonged or repeated exposure

Precautionary Statements

Prevention

Obtain special instructions before use.(P201)

Do not handle until all safety precautions have been

read and understood.(P202)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.(P210)

Keep container tightly closed.(P233) Ground and bond container and receiving equipment.(P240)

Use explosion-proof electrical, ventilating and lighting equipment.(P241)

Use non-sparking tools.(P242)

Take action to prevent static discharges.(P243)

Do not breathe

dust/fume/gas/mist/vapours/spray.(P260)

Avoid breathing

dust/fume/gas/mist/vapours/spray.(P261) Wash hand thoroughly after handling.(P264) Wash eye thoroughly after handling.(P264) Do not eat, drink or smoke when using this product.(P270)

Use only outdoors or in a well-ventilated area.(P271)

Wear protective gloves/protective clothing/eye

protection/face protection.(P280)

Response

IF ON SKIN: Wash with plenty of soap and water.(P302+P352)

IF ON SKIN or hair: Take off immediately all contaminated clothing. Rinse skin with water or

shower.(P303+P361+P353)

IF INHALED: Remove person to fresh air and keep comfortable for breathing.(P304+P340)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.(P305+P351+P338)

IF exposed or concerned: Call a doctor.(P308+P311)

IF exposed or concerned: Get medical advice/attention.(P308+P313)

Call a doctor if you feel unwell.(P312)
Get medical advice and attention if you feel unwell.(P314)

Specific treatment.(P321)

If skin irritation occurs: Get medical advice/attention.(P332+P313)

If eye irritation persists: Get medical advice/attention.(P337+P313)

Take off contaminated clothing and wash it before

reuse.(P362+P364)

In case of fire: Use appropriate media to

extinguish.(P370+P378)

Storage Store in a well-ventilated place. Keep container tightly

closed.(P403+P233)

Store in a well-ventilated place. Keep cool.(P403+P235)

Store locked up.(P405)

Disposal Dispose of contents and container in accordance with

local, regional and national regulations (to be

specified).(P501)

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Distinction of Substance or Mixture

Mixture

Chemical Name or Generic	Concentration or Its	Formula	ENCS No./ISHL No.		CAS RN
Name	Ranges (%)		ENCS No.	ISHL No.	
Methyl ethyl ketone	60-70	CH3CH2CO CH3	(2)-542	Registered	78-93-3
Ethanol	30-less than 40	СН3СН2ОН	(2)-202	Registered	64-17-5
Isopropyl alcohol	1-3	CH3CH(OH)CH3	(2)-207	Registered	67-63-0

Section 4 - FIRST AID MEASURES

IF INHALED: Remove to fresh air and keep at rest in a Inhalation

position comfortable for breathing.

IF exposed or concerned: Call a doctor.

Skin Contact IF ON SKIN (or hair): Remove/Take off immediately all

contaminated clothing. Rinse skin with water/shower.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice and

attention.

Specific treatment.

IF exposed or concerned: Call a doctor.

Eye Contact IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF exposed or concerned: Call a doctor.

Ingestion Rinse mouth.

IF SWALLOWED: Call a doctor if you feel unwell.

IF exposed or concerned: Call a doctor.

Section 5 - FIRE FIGHTING MEASURES

Suitable Extinguishing Use extinguishing agent suitable for type of surrounding Media

fire.

When dust occurs, use dry sand.

Unsuitable Extinguishing

Media

Specific Hazards in Case of Risk of producing harmful gases such as carbon monoxide. Avoid inhalation of smoke or gases.

Specific Fire Fighting Fight fire from upwind position if possible

Keep away from sources of ignition and use appropriate

extinguishing media.

Prohibit unauthorized staff from entering the area

around the fire.

Cylindric water.

Keep unnecessary people away.

Special Protective Use goggles in combination with dust mask, and another

Equipment and Precautions protections as appropriate to situation.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and **Emergency Procedures**

for Fire Fighters

Use goggles in combination with dust mask, and another

protections as appropriate to situation.

Large spills :Evacuate area. Ensure adequate ventilation.

Environmental Precautions Do not discharge into the drains, surface waters or

ground water directly. No information available

Methods and Equipment for Containment and Cleaning

Up

Prevention Measures for Secondary Accidents

Keep away from sources of ignition and prepare

extinguishing media.

Section 7 - HANDLING AND STORAGE

Handling **Technical Measures**

Provide ventilation system and use necessary personal protective equipment as described in "Section 8 -EXPOSURE CONTROLS / PERSONAL PROTECTION".

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Use explosion-proof electrical/ventilating/lighting.

Take precautionary measures against static discharge.

Use local exhaust ventilation in case of production of

fume or mist.

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Precautions for Safe Handling

Keep cool.

Do not breathe dust/fume/gas/mist/vapours/spray.

Do not eat, drink or smoke when using this product.

Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye

protection/face protection.

Prevents Handling of Incompatible

Refer to "Section 10 - STABILITY AND REACTIVITY".

Substances or **Mixtures**

Storage Conditions for Safe

Storage

Refer to "Section 10 - STABILITY AND REACTIVITY".

Store locked up.

Store container tightly closed in well-ventilated place.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

	Japan Administration Level	Exposure Limits (Japan Society for Occupational Health)	Exposure Limits (ACGIH)
Isopropyl alcohol	200ppm	[Maximum allowable concentration] 400ppm (980mg/m3)	TWA 200 ppm, STEL 400 ppm
Methyl ethyl ketone	200ppm	200ppm(590mg/m3)	TWA 200 ppm, STEL 300 ppm
Ethanol	_	-	TWA -, STEL 1000 ppm

Engineering Controls Use local exhaust ventilation in case of production of

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Use explosion-proof electrical equipment and prevent

from static electrocity

Personal Protective

Equipment

Respiratory Protection

If necessary, wear respiratory protection.

Hand Protection Wear protective gloves.

Eye/Face Protection Wear eye protection/face protection.

Skin and Body Protection Wear protective clothing.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State Liquid
Form Liquid
Colour Clear
Odour Solvent odor

Melting Point/Freezing -86.4°C (as 2-Butanone)

Point

Boiling Point or Initial 79.6 °C (as 2-Butanone)

Boiling Point and Boiling

Ranges

Flammability

Lower and Upper Explosion Lower Limit 1.8vol% (as 2-Butanone)

Limit / Flammability Limit

Upper Limit 11.5vol% (as 2-Butanone)

Flash Point -6°C (Tag Closed Cup) Auto-Ignition Temperature 505 $^{\circ}\text{C}$ (as 2-Butanone)

Decomposition No data available

Temperature

pH No data available Kinematic Viscosity 0.5mm2/s

Solubility water: 29g/100mL (20°C) (as 2-Butanone)

Partition Coefficient : n- 0.29(as 2-Butanone)

Octanol/Water

Vapour Pressure 10.5kPa (20°C) (as 2-Butanone)

Density and/or Relative 0.8

Density

Relative Gas Density 2.41 (Air=1, as 2-Butanone)

Particle Characteristics No data available

as Isopropyl alcohol

Boiling Point or Initial 82.4°C

Boiling Point and Boiling

Ranges

Density and/or Relative 0.7863(20°C, 20°C)

Density

as Methyl ethyl ketone

Melting Point/Freezing -86.4°C

Point

Boiling Point or Initial 79.6°C

Boiling Point and Boiling

Ranges

Density and/or Relative 0.8061

Density

as Ethanol

Boiling Point or Initial 78.3°C

Boiling Point and Boiling

Ranges

Density and/or Relative 0.7892(20°C, 4°C)

Density

Section 10 - STABILITY AND REACTIVITY

Reactivity Does not react dangerously under nomal conditions.

Chemical Stability Stable under normal conditions of use.

Possibility of Hazardous Flammable

Reaction

Conditions to Avoid There is a risk of explosion due to impacts, friction, flame and other

source of ignition.

Incompatible Substances or

Mixtures

Hazardous Decomposition

Products

Other Data

No data available

No data available

No data available

Section 11 - TOXICOLOGICAL INFORMATION

Acute Toxicity

Oral

Classified as Not classified since Category 5 is not

adopted in JIS Z 7252.

Dermal Classified as Not classified since ATE is over more than 2000(mg/kg).

Inhalation (gas)

Does not fall under gas based on GHS definitions.

(vapour)

Classified as Category 4 since ATE is 2500 to

20000(ppmV). (dust and mist)

Unable to classify due to insufficient data.

Skin Corrosion/Irritation Classified as Category 2 since the sum of Category 2

ingredients is more than 10%.

Serious Eye Damage/Eye

Irritation

Respiratory Sensitization

Classified as Category 2A since the sum of Eye Category 2A is more than 10%.

Unable to classify due to insufficient data.

Skin Sensitization Unable to classify due to insufficient data. Germ Cell Mutagenicity Unable to classify due to insufficient data.

Classified as Category 1A since one of the Category 1A Carcinogenicity

ingredients is more than 0.1%.

Reproductive Toxicity (Reproductive toxicity)

Classified as Category 1A since one of the Category 1A

ingredients is more than 0.3%.

(Reproductive toxicity, effects on or via lactation)

Unable to classify due to insufficient data.

Specific Target Organ Classified as Category 2(systemic toxicity) since one of Toxicity (Single Exposure) the Category 1(systemic toxicity) ingredients is 1 to

10%.

Classified as Category 2(central nervous system) since one of the Category 1(central nervous system)

ingredients is 1 to 10%.

Classified as Category 2(kidney) since one of the Category 2(kidney) ingredients is more than 10%. Classified as Category 3(respiratory tract irritation) since the sum of Category 3(respiratory tract irritation)

ingredients is more than 20%.

Classified as Category 3(narcotic effect) since the sum of Category 3(narcotic effect) ingredients is more than

20%.

Specific Target Organ Classified as Category 2(blood) since one of the Category 1(blood) ingredients is 1 to 10%.

Toxicity (Repeated Exposure)

> Classified as Category 1(nervous system) since one of the Category 1(nervous system) ingredients is more

than 10%.

Classified as Category 1(liver) since one of the Category 1(liver) ingredients is more than 10%.

Classified as Category 2(central nervous system) since one of the Category 2(central nervous system)

ingredients is more than 10%.

Aspiration Hazard Unable to classify due to insufficient data.

Section 12 - ECOLOGICAL INFORMATION

Hazardous to the Aquatic Classified as Not classified since the sum of $(M \times 100 \times 100)$

Environment, Short-Term Category 1) + (10 × Category 2) + Category 3

(Acute) ingredients is less than 25%.

Hazardous to the Aquatic Classified as Not classified since the sum of $(M \times 100 \times 100)$

Environment, Long-Term Category 1) + (10 × Category 2) + Category 3

(Chronic) ingredients is less than 25%.

Ecotoxicity

Persistence

Bioaccumulative Potential

No data available

No data available

Mobility in Soil No data available

Hazardous to the Ozone Unable to classify due to insufficient data.

Layer

Section 13 - DISPOSAL CONSIDERATIONS

Residual waste

Because waste materials such as liquid waste, paper towels used to wipe it up, or empty containers are flammable combustible materials, the section on "specially controlled industrial waste(Flammable waste oil)" from the Waste Management and Public Cleaning Law (Waste Management Law) is applicable.

Either appropriately process in accordance with Waste Management and Public Cleaning Law, or commission a contractor licensed for transport or disposal of industrial waste requiring special management.

Do not let wastewater, etc. used for cleaning machinery or containers flow directly onto the groundor in to the culverts. For waste materials generated by wastewater treatment, incineration, etc. either carry out processingin accordance with the Waste Management and Public Cleaning Law and related laws and regulations, or commission a licensed vendor to do so.

When incinerating of waste materials, etc., do not use an incinerator without cleaning equipment, as harmful gas will be generated.

Clarify the contents of waste materials and entrust disposal to a waste disposal company.

Contaminated containe Empty containers should be treated as industrial wastes and not allowed to contain waste.

Section 14 - TRANSPORT INFORMATION

International Regulations Regulatory Conform to the provisions of IMO.

Information by Sea

UN No. 1210

Proper Shipping Name PRINTING INK RELATED MATERIAL

Class 3
Packing Group II

Marine Pollutant Not applicable Liquid Substance Not applicable

Transported in Bulk According to MARPOL 73/78, Annex II, the IBC

Code

Regulatory Conform to the provisions of ICAO/IATA.

Information by Air

UN No. 1210

Proper Shipping Name PRINTING INK RELATED MATERIAL

Class 3
Packing Group II

Regulations in Japan Regulatory Complies with the Fire Service Act.

Information by Road

Regulatory Conform to the provisions of the Ship Safety Law.

Information by Sea

UN No. 1210

Proper Shipping Name PRINTING INK RELATED MATERIAL

Class 3 Packing Group Π

Marine Pollutant Not applicable Liquid Substance Not applicable

Transported in Bulk According to MARPOL 73/78, Annex II, the IBC Code

Regulatory

Conform to the provisions of the Civil Aeronautics Law.

Information by Air

UN No.

Proper Shipping Name PRINTING INK RELATED MATERIAL

Class 3 П Packing Group 130

Emergency Response Guide

Number

Section 15 - REGULATORY INFORMATION

Industrial Safety and Health

Ordinance on the Prevention of Organic Solvent Poisoning Paragraph 1 Article 1 part 4 (Second-class organic solvents, etc.),

Enforcement Ordinance 2 of Appendix 6

the standards for work environment monitoring Article 65 part 2-1

Dangerous or Harmful Substances Subject to Be Indicated their

Names, etc.

(Article 57 part 1 Order Article 18 part 1 and 2. Attached Table9)

Dangerous Substances -Flammable substances(Order Article Appended Table 1 part 4)

Hazardous Substances to be notified in terms of Whose Names, etc .(Article 57 part 2, Order Article 18 part 2-1 and part 2, Attached Table9)

Ethanol (Number: 61) (30%-40%)

Propyl alcohol (Number: 494) (less than 5%) Methyl ethyl ketone (Number: 570) (60%-70%)

Materials for special medical examinations and current handling workers(Industrial Safety and Health Act66 2 and Order for Enforcement of Industrial Safety and Health Act Article 22 (i))

Poisonous and Deleterious Substances Control Act Act on Confirmation, etc. of Release Amounts of Specific Chemical Substances in the **Environment and Promotion**

of Improvements to the Management Thereof

Act on the Regulation of Manufacture and Evaluation Not applicable Not applicable

Priority Assessment Chemical Substances(Article 2 part 5)

of Chemical Substances

Hazardous Materials Category IV inflammable liquids Class I

petroleums water-soluble Packing Group II

Narcotics and raw materials for Narcotics or Psychotropics(Appended Table IV part

Psychotropics Control Act 9. Order Article 4)

Foreign Exchange and Import Trade Control Order Appended Table I part 16

Foreign Trade Act

Fire Service Act

Import Trade Control Order Appended Table II (Import Approval)

Ship Safety Law Flammable liquids(Order Article 3,Appended Table I) **Aviation Law** Flammable liquids(Order Article 194,Appended Table I)

Section 16 - OTHER INFORMATION

Industrial Safety and Health Act

Second-class organic solvents, etc.contain more than 5% of Second-class organic solvents.

In the "15. Applicable laws" column, the materials for which label and SDS will be mandated are also listed. (Substance without a decree number.) Reiwa based on 0111 No. 1 from the Kiankahatsu, on January 11, 2022.)

2-butanone and methyl ethyl ketone, MEK and ethyl methyl ketone are the same substances.

Isopropyl alcohol belongs to propyl alcohol.

Act on the Regulation of Manufacture and Evaluation of Chemical Substances

We have a Priority Assessment Chemical Substance posting threshold of 0.1% or more.

The posting of a Priority Assessment Chemical Substance in SDS is as of November 2019 as an effort.

Foreign Exchange and Foreign Trade Act

Foreign Exchange and In law, printing inks are not approved for export

Fire Service Act Poisonous and Deleterious Substances Control

The flash point of Class I petroleums is less than 21 $^\circ$ c. The deleterious substances is only applicable to the material, and

the mixture is non-applicable.

RoHS Specified

Substances treated as equipment are exempt from this law. Cd<100ppm Pb, Hg, Cr(VI), PBB, PBDE, DEHP, DBP, BBP, DIBP <1000ppm

Concentration Allowable concentration Standards

Substance

TLV-TWA: Threshold Limit Values-Time Weighted Average STEL (Short Term Exposure Limit

JIS Z7253:2019

Cited Literature 1) International Chemical Safety Cards

2) National Institute of Technology and Evaluation (NITE), Japan

3) Site for Safe Workplace by Ministry of Health, Labour and Welfare, Japan4) EZSDS (JCDB)

4) E4

Additional Information about This Product:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.