Issue 2005.08.31 Revision 2023.03.07

Safety Data Sheet (SDS)

Section 1 - CHEMICALS AND COMPANY IDENTIFICATION

Chemical Identifier Solvent-73 Product Code TH-73 Reference Number 1011

Name of Supplier Hitachi Industrial Equipment Systems Co.,Ltd.

Address 1-1 Higashitaga-cho 1-chome, Hitachi-shi, Ibaraki-ken,

316-8502 Japan

Company Contact IJP ink Group, Marking Systems and Hoist Systems Division

Phone Number +81-294-36-8682 Fax Number +81-294-36-8975

ogino-masahiko@hitachi-ies.co.jp Mail Address

Emergency Phone +81-294-36-8682

Number

Recommended Use Industrial ink jet printers

Section 2 - HAZARDS IDENTIFICATION

GHS Classification of the Chemical

Physicochemical Flammable liquids Category 2

Health Hazards Acute toxicity (Inhalation: vapour) Category 4

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Carcinogenicity Category 1A Reproductive toxicity Category 1A

Specific target organ toxicity (single exposure) Category 2(visual organ kidney systemic toxicity

central nervous system)

Specific target organ toxicity (single exposure) Category 3(narcotic effect respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Category 1 (nervous system)

Specific target organ toxicity (repeated exposure) Category 2(liver visual organ central nervous system

hearing organ)

Other hazards than mentioned above are Not classified

or Classification not possible.

GHS Label Elements

Pictograms



Signal Word Hazard Statements

Danger

H225 Highly flammable liquid and vapour

H315 Causes skin irritation

H319 Causes serious eye irritation

H332 Harmful if inhaled

H335 May cause respiratory irritation H336 May cause drowsiness or dizziness

H350 May cause cancer

H360 May damage fertility or the unborn child H371 May cause damage to visual organ, kidney, systemic toxicity, central nervous system

H372 Causes damage to nervous system through

prolonged or repeated exposure

H373 May cause damage to liver, visual organ, central nervous system, hearing organ through prolonged or repeated exposure

Precautionary Statements

Prevention

Obtain special instructions before use.(P201)

Do not handle until all safety precautions have been

read and understood.(P202)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.(P210)

Keep container tightly closed.(P233) Ground and bond container and receiving equipment.(P240)

Use explosion-proof electrical, ventilating and lighting equipment.(P241)

Use non-sparking tools.(P242)

Take action to prevent static discharges.(P243)

Do not breathe

dust/fume/gas/mist/vapours/spray.(P260)

Avoid breathing

dust/fume/gas/mist/vapours/spray.(P261) Wash hand thoroughly after handling.(P264) Wash eye thoroughly after handling.(P264) Do not eat, drink or smoke when using this product (P270)

product.(P270)

Use only outdoors or in a well-ventilated area.(P271)

Wear protective gloves/protective clothing/eye

protection/face protection.(P280)

Response

IF ON SKIN: Wash with plenty of soap and water.(P302+P352)

IF ON SKIN or hair: Take off immediately all contaminated clothing. Rinse skin with water or shower.(P303+P361+P353)

IF INHALED: Remove person to fresh air and keep comfortable for breathing.(P304+P340)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.(P305+P351+P338)

IF exposed or concerned: Call a doctor.(P308+P311)

IF exposed or concerned: Get medical advice/attention.(P308+P313)

Call a doctor if you feel unwell.(P312) Get medical advice and attention if you feel unwell.(P314)

Specific treatment.(P321)

If skin irritation occurs: Get medical advice/attention.(P332+P313)

If eye irritation persists: Get medical advice/attention.(P337+P313)

Take off contaminated clothing and wash it before

reuse.(P362+P364)

In case of fire: Use appropriate media to

extinguish.(P370+P378)

Storage Store in a well-ventilated place. Keep container tightly

closed.(P403+P233)

Store in a well-ventilated place. Keep cool.(P403+P235)

Store locked up.(P405)

Disposal Dispose of contents and container in accordance with

local, regional and national regulations (to be

specified).(P501)

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Distinction of Substance or Mixture

Mixture

Chemical Name or Generic	Concentration or Its	Formula	ENCS No./ISHL No.		CAS RN
Name	Ranges (%)		ENCS No.	ISHL No.	
Methyl ethyl ketone	85-90	CH3CH2CO CH3	(2)-542	Registered	78-93-3
Methanol	1-3	СНЗОН	(2)-201	Registered	67-56-1
Ethanol	5-10	СН3СН2ОН	(2)–202	Registered	64-17-5
1-Butanol	3-5	CH3CH2CH 2CH2O H	(2)-3049	Registered	71-36-3

Section 4 - FIRST AID MEASURES

Inhalation IF INHALED: Remove to fresh air and keep at rest in a

position comfortable for breathing.

IF exposed or concerned: Call a doctor. Skin Contact IF ON SKIN (or hair): Remove/Take off immediately all

contaminated clothing. Rinse skin with water/shower.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice and

attention.

Specific treatment.

IF exposed or concerned: Call a doctor.

Eye Contact IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF exposed or concerned: Call a doctor.

Ingestion Rinse mouth.

IF SWALLOWED: Call a doctor if you feel unwell.

IF exposed or concerned: Call a doctor.

Section 5 - FIRE FIGHTING MEASURES

Suitable Extinguishing Use extinguishing agent suitable for type of surrounding Media

When dust occurs, use dry sand. Cylindric water.

Unsuitable Extinguishing

Media

Specific Hazards in Case of Risk of producing harmful gases such as carbon

Fire monoxide. Avoid inhalation of smoke or gases. Specific Fire Fighting Fight fire from upwind position if possible

Keep away from sources of ignition and use appropriate

extinguishing media.

Prohibit unauthorized staff from entering the area

around the fire.

Keep unnecessary people away.

Special Protective Use goggles in combination with dust mask, and another

protections as appropriate to situation.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and **Emergency Procedures**

Equipment and Precautions

for Fire Fighters

Use goggles in combination with dust mask, and another

protections as appropriate to situation.

Large spills :Evacuate area.

Ensure adequate ventilation.

Environmental Precautions Do not discharge into the drains, surface waters or

ground water directly.

No information available

Methods and Equipment for Containment and Cleaning

Up

Prevention Measures for Secondary Accidents

Keep away from sources of ignition and prepare

extinguishing media.

Section 7 - HANDLING AND STORAGE

Handling Technical Measures

Provide ventilation system and use necessary personal protective equipment as described in "Section 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION".

Ground/bond container and receiving equipment. Use only non-sparking tools.

Use explosion-proof electrical/ventilating/lighting.

Take precautionary measures against static discharge.

Use local exhaust ventilation in case of production of fume or mist.

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Precautions for Safe

Handling

Do not breathe dust/fume/gas/mist/vapours/spray.

Do not eat, drink or smoke when using this product.

Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye

protection/face protection.

Refer to "Section 10 - STABILITY AND REACTIVITY".

Prevents Handling of

Incompatible Substances or Mixtures

Conditions for Safe

Storage

Refer to "Section 10 - STABILITY AND REACTIVITY".

Store locked up.

Keep cool.

Store container tightly closed in well-ventilated place.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

	Japan Administration Level	Exposure Limits (Japan Society for Occupational Health)	Exposure Limits (ACGIH)
1-Butanol	25ppm	[Maximum allowable concentration:] 50ppm (150mg/m3) (skin)	TWA 20 ppm, STEL -
Methanol	200ppm	200ppm(260mg/m3)(skin)	TWA 200 ppm, STEL 250 ppm (Skin)
Methyl ethyl ketone	200ppm	200ppm(590mg/m3)	TWA 200 ppm, STEL 300 ppm
Ethanol	-	-	TWA -, STEL 1000 ppm

Engineering Controls

Storage

Use local exhaust ventilation in case of production of

fume or mist.

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Use explosion-proof electrical equipment and prevent

from static electrocity

Personal Protective Respiratory If necessary, wear respiratory protection. Equipment

Hand Protection Wear protective gloves.

Eye/Face Protection Wear eye protection/face protection.

Skin and Body Wear protective clothing.

Protection

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State Liquid
Form Liquid
Colour Clear
Odour Solvent odor

Melting Point/Freezing -86.4°C (as 2-Butanone)

Point

Boiling Point or Initial 79.6 °C (as 2-Butanone)

Boiling Point and Boiling

Ranges

Flammability Flammability

Lower and Upper Explosion Lower Limit 1.8vol% (as 2-Butanone)

Limit / Flammability Limit

Upper Limit 11.5vol% (as 2-Butanone)

Flash Point -4° C (Tag Closed Cup) Auto-Ignition Temperature 505°C (as 2-Butanone)

Decomposition No data available

Temperature

pH No data available Kinematic Viscosity 0.5mm2/s

Solubility water: 29g/100mL (20°C) (as 2-Butanone)

Partition Coefficient : n- 0.29(as 2-Butanone)

Octanol/Water

Vapour Pressure 10.5kPa (20°C) (as 2-Butanone)

Density and/or Relative 0.81

Density

Relative Gas Density 2.41 (Air=1, as 2-Butanone)

Particle Characteristics No data available

as 1-Butanol

Boiling Point or Initial 117.7°C

Boiling Point and Boiling

Ranges

Density and/or Relative 0.81337(15°C, 4°C), 0.80978(20°C, 4°C)

Density as Methanol

Melting Point/Freezing -93.9°C

Point

Boiling Point or Initial 64.1°C, 59.4°C(610mmHg), 39.9°C(260mmHg), 15°C

Boiling Point and Boiling (73mml

Ranges

Density and/or Relative $0.866(-59^{\circ}\text{C}/4^{\circ}\text{C}), \ 0.81(0^{\circ}\text{C}/4^{\circ}\text{C}), \ 0.8006(10^{\circ}\text{C}/4^{\circ}\text{C}),$

Density 0.7910(20°C), 0.7964(15°C/15°C)

as Methyl ethyl ketone

Melting Point/Freezing -86.4°C

Point

Boiling Point or Initial 79.6°C

Boiling Point and Boiling

Ranges

Density and/or Relative 0.8061

Density as Ethanol

Boiling Point or Initial

Boiling Point and Boiling

Ranges

0.7892(20°C, 4°C) Density and/or Relative

Density

Section 10 - STABILITY AND REACTIVITY

Reactivity Does not react dangerously under nomal conditions.

78.3°C

Chemical Stability Stable under normal conditions of use.

Possibility of Hazardous Flammable Reaction

Conditions to Avoid There is a risk of explosion due to impacts, friction, flame and other

source of ignition. No data available

Incompatible Substances or

Mixtures

Hazardous Decomposition No data available

Products Other Data

No data available

Section 11 - TOXICOLOGICAL INFORMATION

Acute Toxicity Oral

Classified as Not classified since ATE is more than

2000(mg/kg).

Classified as Not classified since ATE is more than Dermal

2000(mg/kg).

Inhalation (gas)

Does not fall under gas based on GHS definitions.

Classified as Category 4 since ATE is 2500 to

20000(ppmV). (dust and mist)

Classification not possible since lots of the concentrations of unknown ingredients.

Skin Corrosion/Irritation Classified as Category 2 since the sum of Category 2

ingredients is more than 10%.

Category 2A is more than 10%.

Serious Eye Damage/Eye Classified as Category 2A since the sum of Eye

Irritation

Respiratory Sensitization Unable to classify due to insufficient data.

Skin Sensitization Classification not possible since lots of the

concentrations of unknown ingredients.

Germ Cell Mutagenicity Classification not possible since lots of the

concentrations of unknown ingredients.

Carcinogenicity Classified as Category 1A since one of the Category 1A

ingredients is more than 0.1%.

Reproductive Toxicity (Reproductive toxicity)

Classified as Category 1A since one of the Category 1A

ingredients is more than 0.3%.

(Reproductive toxicity, effects on or via lactation)

Unable to classify due to insufficient data.

Specific Target Organ Classified as Category 2(visual organ) since one of the Toxicity (Single Exposure) Category 1(visual organ) ingredients is 1 to 10%.

> Classified as Category 2(systemic toxicity) since one of the Category 1(systemic toxicity) ingredients is 1 to

Classified as Category 2(central nervous system) since

one of the Category 1(central nervous system)

ingredients is 1 to 10%.

Classified as Category 2(kidney) since one of the Category 2(kidney) ingredients is more than 10%.

Classified as Category 3(narcotic effect) since the sum of Category 3(narcotic effect) ingredients is more than 20%.

Classified as Category 3(respiratory tract irritation) since the sum of Category 3(respiratory tract irritation) ingredients is more than 20%.

Classified as Category 2(central nervous system) since one of the Category 1(central nervous system) ingredients is 1 to 10%.

Classified as Category 2(hearing organ) since one of the Category 1(hearing organ) ingredients is 1 to 10%.

Classified as Category 2(visual organ) since one of the Category 1(visual organ) ingredients is 1 to 10%.

Classified as Category 1(nervous system) since one of the Category 1(nervous system) ingredients is more than 10%.

Classified as Category 2(liver) since one of the Category 1(liver) ingredients is 1 to 10%.
Unable to classify due to insufficient data.

Aspiration Hazard

Specific Target Organ Toxicity (Repeated

Exposure)

Section 12 - ECOLOGICAL INFORMATION

Hazardous to the Aquatic Environment, Short-Term

(Acute)

Hazardous to the Aquatic Environment, Long-Term

(Chronic)
Ecotoxicity
Persistence

Bioaccumulative Potential

Mobility in Soil Hazardous to the Ozone

Layer

Classified as Not classified since the sum of $(M \times 100 \times Category 1) + (10 \times Category 2) + Category 3$

ingredients is less than 25%.

Classified as Not classified since the sum of (M \times 100 \times Category 1) + (10 \times Category 2) + Category 3

ingredients is less than 25%.

No data available No data available No data available

No data available

Unable to classify due to insufficient data.

Section 13 - DISPOSAL CONSIDERATIONS
Residual waste

Because waste materials such as liquid waste, paper towels used to wipe it up, or empty containers are flammable combustible materials, the section on "specially controlled industrial waste(Flammable waste oil)" from the Waste Management and Public Cleaning Law (Waste Management Law) is applicable.

Either appropriately process in accordance with Waste Management and Public Cleaning Law, or commission a contractor licensed for transport or disposal of industrial waste requiring special management.

Do not let wastewater, etc. used for cleaning machinery or containers flow directly onto the groundor in to the culverts. For waste materials generated by wastewater treatment, incineration, etc. either carry out processingin accordance with the Waste Management and Public Cleaning Law and related laws and regulations, or commission a licensed vendor to do so.

When incinerating of waste materials, etc., do not use an incinerator without cleaning equipment, as harmful gas will be generated.

Clarify the contents of waste materials and entrust disposal to a waste disposal company.

Contaminated containe Empty containers should be treated as industrial wastes and not allowed to contain waste.

Section 14 - TRANSPORT INFORMATION

International Regulations Regulatory Conform to the provisions of IMO.

Information by Sea

UN No. 1210

Proper Shipping Name PRINTING INK RELATED MATERIAL

Class Π Packing Group

Not applicable Marine Pollutant Liquid Substance Not applicable

Transported in Bulk According to MARPOL 73/78, Annex II, the IBC

Code

Conform to the provisions of ICAO/IATA. Regulatory

Information by Air

UN No. 1210

Proper Shipping Name PRINTING INK RELATED MATERIAL

Class Packing Group Π

Regulatory Regulations in Japan Complies with the Fire Service Act.

Information by Road

Regulatory Conform to the provisions of the Ship Safety Law.

Information by Sea

UN No. 1210

Proper Shipping Name PRINTING INK RELATED MATERIAL

Class 3 Packing Group П

Marine Pollutant Not applicable Liquid Substance Not applicable

Transported in Bulk According to MARPOL 73/78, Annex II, the IBC

Code

Regulatory Conform to the provisions of the Civil Aeronautics Law.

Information by Air

UN No. 1210

Proper Shipping Name PRINTING INK RELATED MATERIAL

Class 3 П Packing Group 130

Emergency Response Guide Number

Section 15 - REGULATORY INFORMATION

Industrial Safety and Health

Act

Ordinance on the Prevention of Organic Solvent Poisoning Paragraph 1 Article 1 part 4 (Second-class organic solvents, etc.),

Enforcement Ordinance 2 of Appendix 6

the standards for work environment monitoring Article 65 part 2-1

Dangerous or Harmful Substances Subject to Be Indicated their

Names, etc.

(Article 57 part 1, Order Article 18 part 1 and 2, Attached Table9)

Dangerous Substances -Flammable substances(Order Article

Appended Table 1 part 4)

Hazardous Substances to be notified in terms of Whose Names, etc .(Article 57 part 2 ,Order Article 18 part 2-1and part 2, Attached

Table9)

Ethanol (Number: 61) (1%-10%) Butanol (Number: 477) (less than 5%) Methanol (Number: 560) (less than 5%) Methyl ethyl ketone (Number: 570) (80%-90%)

Materials for special medical examinations and current handling workers(Industrial Safety and Health Act66 2 and Order for Enforcement of Industrial Safety and Health Act Article 22 (i))

Poisonous and Deleterious Substances Control Act Act on Confirmation, etc. of Release Amounts of Specific Chemical

Substances in the **Environment and Promotion** of Improvements to the

Not applicable

Not applicable

Act on the Regulation of Manufacture and Evaluation of Chemical Substances

Management Thereof

Priority Assessment Chemical Substances(Article 2 part 5)

Fire Service Act

Hazardous Materials Category IV inflammable liquids Class I

petroleums water-soluble Packing Group II

Narcotics and

raw materials for Narcotics or Psychotropics(Appended Table IV part

Psychotropics Control Act

9. Order Article 4) Import Trade Control Order Appended Table I part 16

Foreign Exchange and Foreign Trade Act

Import Trade Control Order Appended Table II (Import Approval)

Ship Safety Law **Aviation Law**

Flammable liquids(Order Article 3,Appended Table I) Flammable liquids(Order Article 194,Appended Table I)

Section 16 - OTHER INFORMATION

Industrial Safety and Health Act

Second-class organic solvents, etc.contain more than 5% of Secondclass organic solvents.

In the "15. Applicable laws" column, the materials for which label and SDS will be mandated are also listed. (Substance without a decree number.) Reiwa based on 0111 No. 1 from the Kiankahatsu, on January 11, 2022.)

2-butanone and methyl ethyl ketone, MEK and ethyl methyl ketone are the same substances.

Act on the Regulation of Manufacture and Evaluation of

We have a Priority Assessment Chemical Substance posting threshold of 0.1% or more.

Chemical Substances

<1000ppm

The posting of a Priority Assessment Chemical Substance in SDS is

as of November 2019 as an effort. Foreign Exchange and In law, printing inks are not approved for export

Foreign Trade Act

Fire Service Act Poisonous and Deleterious Substances Control

The flash point of Class I petroleums is less than 21 $^{\circ}\,$ c. The deleterious substances is only applicable to the material, and the mixture is non-applicable.

Act

Substances treated as equipment are exempt from this law. $Cd \le 100ppm$ Pb, Hg, Cr(VI), PBB, PBDE, DEHP, DBP, BBP, DIBP

RoHS Specified Substance Concentration

Allowable TLV-TWA: Threshold Limit Values-Time Weighted Average STEL (Short Term Exposure Limit

concentration Standards

Cited Literature

JIS Z7253:2019

1) International Chemical Safety Cards

2) National Institute of Technology and Evaluation (NITE), Japan

3) Site for Safe Workplace by Ministry of Health, Labour and Welfare, Japan

4) EZSDS (JCDB)

about This Product:

Additional Information To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.