Issue 2006.08.25 Revision 2022.10.07

Safety Data Sheet (SDS)

Section 1 - CHEMICALS AND COMPANY IDENTIFICATION

Chemical Identifier	Solvent-84/Solvent-S1084
Product Code	TH-84/S1084
Reference Number	1012
Name of Supplier	Hitachi Industrial Equipment Systems Co.,Ltd.
Address	1-1 Higashitaga-cho 1-chome,Hitachi-shi, Ibaraki-ken, 316-8502 Japan
Company Contact	IJP ink Group, Marking Systems and Hoist Systems Division
Phone Number	+81-294-36-8682
Fax Number	+81-294-36-8975
Mail Address	ogino-masahiko@hitachi-ies.co.jp
Emergency Phone	+81-294-36-8682
Number	

Industrial ink jet printers

Number Recommended Use

Section 2 – HAZARDS IDENTIFICATION

GHS Classification of the	e Chemical	
	Physicochemical Health Hazards	Flammable liquids Category 2 Acute toxicity (Inhalation: vapour) Category 4 Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2A Reproductive toxicity Category 1B Specific target organ toxicity (single exposure) Category 2(visual organ kidney systemic toxicity central nervous system)
		Specific target organ toxicity (single exposure) Category 3(narcotic effect respiratory tract irritation)
		Specific target organ toxicity (repeated exposure) Category 1(nervous system)
		Specific target organ toxicity (repeated exposure) Category 2(respiratory apparatus visual organ digestive tract central nervous system)
		Other hazards than mentioned above are Not classified or Classification not possible.
GHS Label Elements	Pictograms	
	Signal Word Hazard Statements	Danger H225 Highly flammable liquid and vapour H315 Causes skin irritation H319 Causes serious eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation H336 May cause drowsiness or dizziness H360 May damage fertility or the unborn child H371 May cause damage to visual organ, kidney, systemic toxicity, central nervous system H372 Causes damage to nervous system through prolonged or repeated exposure H373 May cause damage to respiratory apparatus, visual organ, digestive tract, central nervous system through prolonged or repeated exposure

Precautionary Statements

Prevention	Obtain special instructions before use.(P201) Do not handle until all safety precautions have been
	read and understood.(P202) Keep away from heat, hot surfaces, sparks, open flames
	and other ignition sources. No smoking.(P210)
	Keep container tightly closed.(P233)
	Ground and bond container and receiving equipment.(P240)
	Use explosion-proof electrical, ventilating and lighting equipment.(P241)
	Use non-sparking tools.(P242)
	Take action to prevent static discharges.(P243)
	Do not breathe dust/fume/gas/mist/vapours/spray.(P260)
	Avoid breathing dust/fume/gas/mist/vapours/spray.(P261)
	Wash hand thoroughly after handling.(P264) Wash eye thoroughly after handling.(P264)
	Do not eat, drink or smoke when using this product.(P270)
	Use only outdoors or in a well-ventilated area.(P271)
	Wear protective gloves/protective clothing/eye protection/face protection.(P280)
Response	IF ON SKIN: Wash with plenty of soap and water.(P302+P352)
	IF ON SKIN or hair: Take off immediately all contaminated clothing. Rinse skin with water or shower.(P303+P361+P353)
	IF INHALED: Remove person to fresh air and keep comfortable for breathing.(P304+P340)
	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.(P305+P351+P338)
	IF exposed or concerned: Call a doctor.(P308+P311)
	IF exposed or concerned: Get medical advice/attention.(P308+P313)
	Call a doctor if you feel unwell.(P312)
	Get medical advice and attention if you feel unwell.(P314)
	Specific treatment.(P321)
	If skin irritation occurs: Get medical advice/attention.(P332+P313)
	If eye irritation persists: Get medical advice/attention.(P337+P313)
	Take off contaminated clothing and wash it before reuse.(P362+P364)
	In case of fire: Use appropriate media to extinguish.(P370+P378)
Storage	Store in a well-ventilated place. Keep container tightly closed.(P403+P233)
	Store in a well-ventilated place. Keep cool.(P403+P235)
	Store locked up.(P405)
Disposal	Dispose of contents and container in accordance with local, regional and national regulations (to be specified).(P501)

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Distinction of Substance or Mixture		Mixture			
	Concentration or Its	Formula	ENCS No./I		CAS RN
Name	Ranges (%)		ENCS No.	ISHL No.	70.00.0
Methyl ethyl ketone	90-100	CH3CH2CO CH3	(2)-542	Registered	78-93-3
Methanol	1-3	СНЗОН	(2)-201	Registered	67-56-1
Acetone	1–3	СНЗСОСНЗ	(2)-542	Registered	67-64-1
Ethylene glycol mono-n- butyl ether (alias Butyl cellosolve)	0.1–1	-	(2)-407,(2)- 2424,(7)-97	Registered	111-76-2
tion 4 – FIRST AID MEASUR Inhalation	ES		: Remove to nfortable for		l keep at rest in a
Skin Contact		IF exposed or concerned: Call a doctor. IF ON SKIN (or hair): Remove/Take off immediately al contaminated clothing. Rinse skin with water/shower.			
		IF ON SKIN	: Wash with p	lenty of soa	o and water.
		If skin irritat attention.	tion occurs:	Get medical	advice and
Eye Contact		Specific treatment. IF exposed or concerned: Call a doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy t do. Continue rinsing.			
		If eye irritat	ion persists:		advice/attentior
Ingestion		IF exposed or concerned: Call a doctor. Rinse mouth. IF SWALLOWED: Call a doctor if you feel unwell.			
		IF exposed	or concernec	l: Call a doct	or.
tion 5 – FIRE FIGHTING MEA	SURES				
Suitable Extinguishing Media		fire.	ishing agent occurs, use d		type of surroundi
Unsuitable Extinguishing Media		Cylindric wa	ater.		
Specific Hazards in Case of Fire		Risk of producing harmful gases such as carbon monoxide. Avoid inhalation of smoke or gases.			
Specific Fire Fighting		Fight fire from upwind position if possible Keep away from sources of ignition and use appropriat extinguishing media. Prohibit unauthorized staff from entering the area around the fire.			
Special Protective Equipment and Precautions for Fire Fighters		Keep unnecessary people away. Use goggles in combination with dust mask, and anothe protections as appropriate to situation.			
tion 6 – ACCIDENTAL RELE/ Personal Precautions, Protective Equipment and Emergency Procedures	ASE MEASURES		in combinati as appropria		mask, and anoth n.
Environmental Precautions		Ensure adeo	:Evacuate ar quate ventilat harge into th	tion.	face waters or

ground water directly.

Methods and Equipment fo Containment and Cleaning Up		No information available
Prevention Measures for Secondary Accidents		Keep away from sources of ignition and prepare extinguishing media.
Section 7 - HANDLING AND S	TORAGE	
Handling	Technical Measures	Provide ventilation system and use necessary personal protective equipment as described in "Section 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION".
		Ground/bond container and receiving equipment. Use only non-sparking tools. Use explosion-proof electrical/ventilating/lighting.
		Take precautionary measures against static discharge.
		Use local exhaust ventilation in case of production of fume or mist.
		Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.
	Precautions for Safe Handling	Keep cool.
	U	Do not breathe dust/fume/gas/mist/vapours/spray.
		Do not eat, drink or smoke when using this product.
		Wash hands thoroughly after handling.
		Use only outdoors or in a well-ventilated area.
		Wear protective gloves/protective clothing/eye protection/face protection.
	Prevents Handling of Incompatible Substances or Mixtures	Refer to "Section 10 - STABILITY AND REACTIVITY".
Storage	Conditions for Safe Storage	Refer to "Section 10 - STABILITY AND REACTIVITY".
	5	Store locked up. Store container tightly closed in well-ventilated place.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

	Japan Administration Level	Exposure Limits (Japan Society for Occupational Health)	Exposure Limits (ACGIH)
Acetone	500ppm	200ppm(470mg/m3)	TWA 250 ppm, STEL 500 ppm
Ethylene glycol mono-n- butyl ether (alias Butyl cellosolve)	25ppm	【Maximum allowable concentration: 】 20ppm (97mg/m3) (skin)	TWA 20 ppm, STEL -
Methanol	200ppm	200ppm(260mg/m3)(skin)	TWA 200 ppm, STEL 250 ppm (Skin)
Methyl ethyl ketone	200ppm	200ppm(590mg/m3)	TWA 200 ppm, STEL 300 ppm
Engineering Controls		fume or mist. Facilities storing or utilizi	tion in case of production of ing this material should be h facility and a safety shower.
		Use explosion-proof elec from static electrocity.	trical equipment and prevent
Personal Protective Equipment	Respiratory Protection	If necessary, wear respire	atory protection.
	Hand Protection	Wear protective gloves.	

Eye/Face Protection	Wear eye protection/face protection.
Skin and Body	Wear protective clothing.
Protection	

Section 9 - PHYSICAL AND CHEMICAL PROPERTI Physical State	ES Liquid
Form	Liquid
Colour	Clear
Odour	Solvent odor
Melting Point/Freezing Point	-86.4°C (as 2-Butanone)
Boiling Point or Initial Boiling Point and Boiling Ranges	79.6 ℃ (as 2-Butanone)
Flammability Lower and Upper Explosion Lower Limit Limit / Flammability Limit	Flammability 1.8vol% (as 2-Butanone)
Upper Limit	11.5vol% (as 2-Butanone)
Flash Point	−6.3°C (Tag Closed Cup)
Auto-Ignition Temperature	505°C (as 2-Butanone)
Decomposition Temperature	No data available
рН	No data available
Kinematic Viscosity	0.5mm2/s
Partition Coefficient : n− Octanol/Water	0.29(as 2-Butanone)
Vapour Pressure	10.5kPa (20°C) (as 2–Butanone)
Density and/or Relative Density	0.81
Relative Gas Density	2.41 (Air=1, as 2-Butanone)
Particle Characteristics	No data available
as Acetone Melting Point/Freezing Point	−94.6°C
Boiling Point or Initial Boiling Point and Boiling Ranges	56.5°C
Flash Point	-20°C
Vapour Pressure	180.3mmHg(20°C)
Density and/or Relative Density	0.7898(20°C, 4°C)
as Methanol	
Melting Point/Freezing Point	−93.9°C
Boiling Point or Initial Boiling Point and Boiling Ranges	64.1°C, 59.4°C(610mmHg), 39.9°C(260mmHg), 15°C (73mmHg)
Density and∕or Relative Density	0.866(−59°C/4°C), 0.81(0°C/4°C), 0.8006(10°C/4°C) 0.7910(20°C), 0.7964(15°C/15°C)
as Methyl ethyl ketone	
Melting Point/Freezing Point	-86.4°C
Boiling Point or Initial Boiling Point and Boiling Ranges	79.6°C
Density and/or Relative Density	0.8061
Section 10 - STABILITY AND REACTIVITY	
Reactivity	Does not react dangerously under nomal conditions.

c/	1	$ \land $
6/	Τ	U

Chemical Stability Possibility of Hazardous Reaction Conditions to Avoid		Stable under normal conditions of use. Flammable There is a risk of explosion due to impacts, friction, flame and other
		source of ignition.
Incompatible Substances o Mixtures	r	No data available
Hazardous Decomposition Products		No data available
Other Data		No data available
Section 11 - TOXICOLOGICAL		
Acute Toxicity	Oral	Classified as Not classified since ATE is more than $2000(mg/kg)$.
	Dermal	Classified as Not classified since ATE is more than 2000(mg/kg).
	Inhalation	(gas) Does not fall under gas based on GHS definitions.
		(vapour)
		Classified as Category 4 since ATE is 2500 to 20000(ppmV).
		(dust and mist)
Skin Corrosion/Irritation		Unable to classify due to insufficient data. Classified as Category 2 since the sum of Category 2 ingredients is more than 10%.
Serious Eye Damage/Eye Irritation		Classified as Category 2A since the sum of Eye Category 2A is more than 10%.
Respiratory Sensitization		Unable to classify due to insufficient data.
Skin Sensitization		Classification not possible since lots of the concentrations of unknown ingredients.
Germ Cell Mutagenicity		Classification not possible since lots of the concentrations of unknown ingredients.
Carcinogenicity		Unable to classify due to insufficient data.
Reproductive Toxicity		(Reproductive toxicity) Classified as Category 1B since one of the Category 1B ingredients is more than 0.3%.
		*Category 2 ingredients is contained more than 3.0%.
		*Category 2 ingredients is contained more than 3.0%.
		(Reproductive toxicity, effects on or via lactation)
		Unable to classify due to insufficient data.
Specific Target Organ Toxicity (Single Exposure)		Classified as Category 2(visual organ) since one of the Category 1(visual organ) ingredients is 1.0 to 10%.
		Classified as Category 2(systemic toxicity) since one of the Category 1(systemic toxicity) ingredients is 1.0 to 10%.
		Classified as Category 2(central nervous system) since one of the Category 1(central nervous system) ingredients is 1.0 to 10%.
		Classified as Category 2(kidney) since one of the Category 2(kidney) ingredients is 1.0 to 10%.
		Classified as Category 3(narcotic effect) since the sum of Category 3(narcotic effect) ingredients is more than 20%.
		Classified as Category 3(respiratory tract irritation) since the sum of Category 3(respiratory tract irritation) ingredients is more than 20%.

Specific Target Organ Toxicity (Repeated Exposure)		Classified as Category 2(respiratory apparatus) since one of the Category 1(respiratory apparatus) ingredients is 1.0 to 10%.
		Classified as Category 2(digestive tract) since one of the Category 1(digestive tract) ingredients is 1.0 to 10%.
		Classified as Category 2(visual organ) since one of the Category 1(visual organ) ingredients is 1.0 to 10%.
		Classified as Category 2(central nervous system) since one of the Category 1(central nervous system) ingredients is 1.0 to 10%.
		Classified as Category 1(nervous system) since one of the Category 1(nervous system) ingredients is more than 10%.
Aspiration Hazard		Unable to classify due to insufficient data.
Section 12 - ECOLOGICAL INF	ORMATION	
Hazardous to the Aquatic Environment, Short-Term (Acute)		Classified as Not classified since the sum of $(M \times 100 \times Category 1) + (10 \times Category 2) + Category 3$ ingredients is less than 25%.
Hazardous to the Aquatic Environment, Long-Term (Chronic)		Classified as Not classified since the sum of $(M \times 100 \times Category 1) + (10 \times Category 2) + Category 3$ ingredients is less than 25%.
Ecotoxicity		No data available
Persistence Bioaccumulative Potential		No data available No data available
		N
Mobility in Soil Hazardous to the Ozone Layer		No data available Unable to classify due to insufficient data.
Section 13 - DISPOSAL CONS	IDERATIONS	
	Residual waste	Because waste materials such as liquid waste, paper towels used to wipe it up, or empty containers are flammable combustible materials, the section on "specially controlled industrial waste(Flammable waste oil)" from the Waste Management and Public Cleaning Law (Waste Management Law) is applicable.
		Either appropriately process in accordance with Waste Management and Public Cleaning Law, or commission a contractor licensed for transport or disposal of industrial waste requiring special management.
		Do not let wastewater, etc. used for cleaning machinery or containers flow directly onto the groundor in to the culverts. For waste materials generated by wastewater treatment, incineration, etc. either carry out processingin accordance with the Waste Management and Public Cleaning Law and related laws and
		regulations, or commission a licensed vendor to do so. When incinerating of waste materials, etc., do not use an incinerator without cleaning equipment, as harmful gas will be generated.
		Clarify the contents of waste materials and entrust disposal to a
		waste disposal company.
	Contaminated containe	e Empty containers should be treated as industrial wastes and not allowed to contain waste.
Section 14 – TRANSPORT INF		
International Regulations	Regulatory	Conform to the provisions of IMO.
	Information by Sea UN No.	1210
		PRINTING INK RELATED MATERIAL
	Class	3
	Packing Group	Ш

	Marine Pollutant Liquid Substance Transported in Bulk According to MARPOL 73/78, Annex II, the IBC Code	Not applicable Not applicable
	Regulatory Information by Air UN No. Proper Shipping Name Class	Conform to the provisions of ICAO/IATA. 1210 PRINTING INK RELATED MATERIAL 3
Regulations in Japan	Packing Group Regulatory Information by Road	I Complies with the Fire Service Act.
	Regulatory Information by Sea	Conform to the provisions of the Ship Safety Law.
	Class	1210 PRINTING INK RELATED MATERIAL 3
	Packing Group Marine Pollutant	II Not applicable
	Liquid Substance Transported in Bulk According to MARPOL 73/78, Annex II, the IBC Code	Not applicable
	Regulatory Information by Air	Conform to the provisions of the Civil Aeronautics Law.
	UN No. Proper Shipping Name Class	1210 PRINTING INK RELATED MATERIAL 3
Emergency Response Guide Number	Packing Group	П 130
Section 15 - REGULATORY INF Industrial Safety and Health Act	ORMATION	Ordinance on the Prevention of Organic Solvent Poisoning Paragraph 1 Article 1 part 4 (Second-class organic solvents, etc.), Enforcement Ordinance 2 of Appendix 6 the standards for work environment monitoring Article 65 part 2-1
		Dangerous or Harmful Substances Subject to Be Indicated their Names, etc. (Article 57 part 1 ,Order Article 18 part 1 and 2, Attached Table9)
		Dangerous Substances -Flammable substances(Order Article Appended Table 1 part 4)
		Hazardous Substances to be notified in terms of Whose Names,etc .(Article 57 part 2 ,Order Article 18 part 2-1and part 2, Attached Table9)
		Acetone(Number:17)(less than 5%) Ethylene glycol mono-n-butyl ether (alias Butyl cellosolve) (Number:79)(less than 5%)
		Methanol(Number:560) (less than 5%) Methyl ethyl ketone(Number:570) (more than 90%)
		Materials for special medical examinations and current handling workers(Industrial Safety and Health Act66 2 and Order for Enforcement of Industrial Safety and Health Act Article 22 (i))
Poisonous and Deleterious Substances Control Act		Not applicable

	Act on Confirmation, etc. of Release Amounts of Specific Chemical Substances in the Environment and Promotion of Improvements to the Management Thereof		Not applicable
	Act on the Regulation of Manufacture and Evaluation of Chemical Substances		Priority Assessment Chemical Substances(Article 2 part 5)
	Fire Service Act		Hazardous Materials Category IV inflammable liquids Class I petroleums non water-soluble Packing Group II
	Narcotics and Psychotropics Control Act Foreign Exchange and Foreign Trade Act		raw materials for Narcotics or Psychotropics(Appended Table IV part 9, Order Article 4)
			Import Trade Control Order Appended Table I part 16
			Import Trade Control Order Appended Table ${\ensuremath{\mathbb I}}$ (Import Approval)
	Ship Safety Law Aviation Law		Flammable liquids(Order Article 3,Appended Table I) Flammable liquids(Order Article 194,Appended Table I)
Section 16 - OTHER INFORMATION			
		Industrial Safety and Health Act	Second-class organic solvents, etc.contain more than 5% of Second- class organic solvents.
			In the "15. Applicable laws" column, the materials for which label and SDS will be mandated are also listed. (Substance without a decree number.) Reiwa based on 0111 No. 1 from the Kiankahatsu, on January 11, 2022.)
			2-butanone and methyl ethyl ketone, MEK and ethyl methyl ketone are the same substances.
			2-Butoxyethanol, ethylene glycol mono-normal-butyl ether, ethylene glycol monobutyl ether, butyl cellosolve is the same substance.
		Act on the Regulation of Manufacture and Evaluation of Chemical Substances	We have a Priority Assessment Chemical Substance posting threshold of 0.1% or more.
			The posting of a Priority Assessment Chemical Substance in SDS is as of November 2019 as an effort.
		Foreign Exchange and Foreign Trade Act	In law, printing inks are not approved for export
		Fire Service Act Poisonous and Deleterious Substances Control Act	The flash point of Class I petroleums is less than 21 \degree c. The deleterious substances is only applicable to the material, and the mixture is non-applicable.
		RoHS Specified Substance Concentration	Cd<100ppm Pb, Hg, Cr(VI), PBB, PBDE, DEHP, DBP, BBP, DIBP <1000ppm
		Allowable concentration Standards Cited Literature	TLV-TWA: Threshold Limit Values-Time Weighted Average STEL (Short Term Exposure Limit JIS Z7253:2019 1) International Chemical Safety Cards
			2) National Institute of Technology and Evaluation (NITE), Japan
			 3) Site for Safe Workplace by Ministry of Health, Labour and Welfare, Japan 4) EZSDS(JCDB)

Additional Information about This Product: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.