



## Blowers

### Vortex blower

High air pressure compact  
type(G series)



VB-70WS-G ~ VB-022-G  
100V, single-phase, 50/60Hz  
200V, three-phase, 50/60Hz  
400V, three-phase, 50/60Hz  
Maximum air capacity :  
0.45/0.5 ~ 4.5/5.5(m<sup>3</sup>/min)  
Maximum static pressure :  
4.0/5.4 ~ 19.6/23.5(kPa)

Air capacity type  
(E, E2 series)



VB-001S-E ~ VB-110-E2  
100V, single-phase, 50/60Hz  
200V, three-phase, 50/60Hz  
400V, three-phase, 50/60Hz  
Maximum air capacity :  
0.65/0.75 ~ 16/18.5(m<sup>3</sup>/min)  
Maximum static pressure :  
4.6/6.2 ~ 25.5/29.4(kPa)

DN series



VB-004DN ~ VB-020DN  
100V, single-phase, 50/60Hz  
200V, three-phase, 50/60Hz  
400V, three-phase, 50/60Hz  
Maximum air capacity:  
1.4/1.8 ~ 3.5/4.2 (m<sup>3</sup>/min)  
Maximum static pressure:  
11.1/12.7 ~ 18.0/20.0 (kPa)

Products in this catalogue are not available in some regions. Ask each sales office for the detail.