



Programmable Controllers



EH-150/EHV

EHV-CPU128/64/32/16
 Processing speed:20ns
 I/O points:Max.4,224
 Program Memory:Max.128k steps
 Comment Memory:Max.1Mbyte
 Integrated Ethernet/Serial/USB
 communication ports
 7 Segment LED error display



EH-ETH2
 Ethernet™
 Module




EH-RMD
 DeviceNet™
 Module



EH-RMP
 PROFIBUS®
 Module



EH-SIO
 Serial
 Communication
 Module



**Programming Software for EHV:
 Control Editor**
 (Japanese/English/Simplified
 Chinese/Traditional Chinese Version)



EH-150

Processing speed:
 1.0 μs/0.1 μs/command
 I/O points: Max. 3,520
 Program Memory: 4/8/16/48k steps
 Two communication ports
 Compact design with 10cm in height



MICRO-EH(Board type)

Processing speed:0.9 μs
 I/O points:10/14/20/23/28/40/64
 Program Memory:3k steps/16k steps
 Selectable option boards
 (serial/Ethernet/USB)



H-302/H-702/H-1002/H-2002

I/O points: Max.7,936(H-2002)
 Program Memory:
 Max. 48.5k steps(H-2002)



LADDER EDITOR for Windows®
 (For EH/H series)
 Ladder/command language
 programming software

HLW-PCRE
 (Windows® 2000/XP)

Products in this catalogue are not available in some regions. Ask each sales office for the detail.